

UNIVERSAL COMMERCIAL FIRE COMMUNICATOR





MQ03-LTE-M-EN54



FUTURE-PROOF TECHNOLOGY

Dual-SIM device, each SIM supporting multiple operators per country



FAST AND EASY INSTALLATION

with any panel using Contact ID, SIA and Pulse 4+2



RELIABLE DATA REPORTING

to any Alarm Receiving Center



IMPROVED RECURRING REVENUE

Low flat-rate monthly fees for improved profitability



MAIN FEATURES

REPORTING FORMATS - Dial Capture Interface supporting Contact ID, SIA and Pulse 4+2

EXCEPTIONAL REDUNDANCY – Dual-SIM device, each SIM supporting multiple operators per country

SUPERVISED CONNECTIVITY – 10 minute polling of the connection

ADMIN PORTAL - Online 24/7 device management & real-time status monitoring of user accounts

FULL EVENT REPORTING - Reliable reporting to any Alarm Receiving Center

INSTALLER MOBILE APP – Real-time on-site communication diagnostics and device configuration

UNIVERSAL PANEL COMPATIBILITY - Support of any panel via dial capture interface or digital inputs

SPECIFICATIONS

- Multi-band CAT-M1 LTE 700/850/1700/1900/2100 MHz
- Dial Capture Interface: CID, SIA, Pulse 4+2
- 4 inputs & 2 outputs (programmable)
- Supply voltage: +12 to +29 VDC
- Consumption: Standby 50mA, Peak 200mA
- Dimensions: 63 x 90 x 32 mm
- · Weight: 73g without antenna

CERTIFICATIONS

- EN54-21
- RED

RCONTROL ADMIN MOBILE APP 24 LIN VOCATORE 25,801 N1 AND AND AND AND AND AND AND AND COTT OUT? Device Details Many Hard Seriable Propriet From the Cottle for Accordance And COCHERNEY From the Cottle f